Datenblatt

RED®

ÜBERZEUGT. EINFACH.

Wärmeschrumpfschlauch 3:1 Box 18/6 mm, schwarz, 4 m



4 046725 357933

Leistungsmerkmale

Der dünnwandige Wärmeschrumpfschlauch 3:1 aus vernetztem Polyolefin ist flexibel und flammwidrig. Dank der idealen Schrumpfrate 3:1 decken diese Schrumpfschläuche mit nur wenigen Größen einen breiten Anwendungsbereich ab.

Die Lieferung des RED Wärmeschrumpfschlauchs erfolgt in einer praktischen Spenderbox. Das auf der Kartonage integrierte Zentimetermaß ermöglicht es, Abschnitte schnell und präzise für die aktuell auszuführende Arbeit abzumessen und abzuschneiden. Die Box ist zudem bei Transport sowie Lagerung platzsparend und hält die Ware frei von Staub und Schmutz. Perfekt für variierende Isolierungsarbeiten im Werk oder vor Ort.

Technische Daten:

- Lagerung: -10 °C bis +40 °C, rel. Luftfeuchtigkeit: <75 %
- Haltbarkeit: 24 Monate

DEHA-Nummer

5116536

Artikelnummer

2230-10-0006

EAN

4046725357933

Kennzeichnung


GEWÄHRLEISTUNG 5 JAHRE


Wärmeschrumpfschlauch 3:1 Box 18/6 mm, schwarz, 4 m


Allgemeine Daten

Merkmale	
Typ	Warmschrumpf
Ausführung	dünnwandig
Schrumpfrate	3:1
Innendurchmesser vor Schrumpf	18 mm
Innendurchmesser nach Schrumpf	6 mm
Nenndurchmesser in Zoll	3/4
Wandstärke nach Schrumpf	0,9 mm
Länge	4 m
Betriebstemperatur	-55 - 125 °C
Farbe	schwarz
Werkstoff	Polyolefin
UL-Zulassung	ja

Produktabbildungen







Bestelldaten

DEHA-Nr.	Typ	Artikelnummer	EAN	VPE
5116536	WSB 3:1 Box 18.0-6.0	2230-10-0006	4046725357933	1 Stück

Data Sheet

RED®

SIMPLY. CONVINCING.

Heat-shrink tubing 3:1 Box, 18/6 mm, black, 4 m



4 046725 357933

Performance features

The thin-walled 3:1 cross-linked polyolefin heat-shrink tubing is flexible and flame-retardant. Thanks to the ideal shrink ratio of 3:1, these shrink tubes cover a wide range of applications with just a few sizes.

The RED heat shrink tubing is delivered in a practical dispenser box. The centimeter ruler integrated on the cardboard box makes it possible to quickly and precisely measure and cut sections for the current work to be carried out. The box also saves space during transport and storage and keeps the goods free of dust and dirt. Perfect for varied insulation work at the factory or on site.

Technical specifications:

- Storage: -10 °C to +40 °C, rel. Humidity: <75%
- Shelf life: 24 months

DEHA number

5116536

Item number

2230-10-0006

EAN

4046725357933

label


GEWÄHRLEISTUNG 5 JAHRE


Heat-shrink tubing 3:1 Box, 18/6 mm, black, 4 m


General Data

Features	
Type	Heat-shrink
Model	Thin-walled
Shrink rate	3:1
Inner diameter before heat-shrink	18 mm
Inner diameter after heat-shrink	6 mm
Nominal diameter inch	3/4
Wall thickness after shrinking	0,9 mm
Length	4 m
Operation temperature	-55 - 125 °C
Colour	Black
Material	Polyolefin
UL approval	yes

Product pictures







Order Data

DEHA no	Type	Item number	EAN	VPE
5116536	WSB 3:1 Box 18.0-6.0	2230-10-0006	4046725357933	1 Piece