Datenblatt

RED®

ÜBERZEUGT. EINFACH.

Aderendhülsen, isoliert, 1,5 mm², 8 mm, schwarz



4 046725 357995

Leistungsmerkmale

Die isolierten Aderendhülsen garantieren eine optimale elektrische Verbindung zwischen Leiter und Kabelklemme sowie eine einfache Montage. Gratfreie Ausführung in Länge 6–8 mm, mit Aufweitung, zur einfachsten und spleißfreien Kabeleinführung.
Material: Hülse aus Kupfer gefertigt, in galvanisch verzinnter Ausführung für höchstmöglichen Korrosionsschutz.
Die Isolation aus Polypropylen garantiert eine hohe Lebensdauer und Bruchsicherheit. Extreme Temperaturbeständigkeit für Schaltschrankumgebungsbedingungen bis 105 °C. Ausführung der Farbgebung und Abmessungen gemäß DIN 46228 Teil 4.

DEHA-Nummer

5150263

Artikelnummer

2250-30-0005

EAN

4046725357995

Kennzeichnung

Aderendhülsen, isoliert, 1,5 mm², 8 mm, schwarz

Allgemeine Daten

Merkmale	
Bauform	Standard
Nennquerschnitt	1,5 qmm
Hülsenlänge	8 mm
Isoliert	ja
Halogenfrei	ja
Farbe	schwarz
Werkstoff	Kupfer
Oberfläche	verzinnt

Produktabbildungen

Bestelldaten

DEHA-Nr.	Typ	Artikelnummer	EAN	VPE
5150263	2250-30-0005	2250-30-0005	4046725357995	1000 Stück

Data Sheet

RED®

SIMPLY. CONVINCING.

Ferrules, insulated, 1.5mm², 8 mm, black



4 046725 357995

Performance features

The insulated ferrules guarantee an optimal electrical connection between conductor and cable clamp as well as easy assembly. Burr-free version with a length of 6-8 mm, with expansion, for the simplest and splice-free cable entry. Material: Sleeve made of copper, tin-plated for the best possible protection against corrosion.
The polypropylene insulation guarantees a long service life and resistance to breakage. Extreme temperature resistance for control cabinet ambient conditions up to 105 °C. Execution of the coloring and dimensions according to DIN 46228 part 4.

DEHA number

5150263

Item number

2250-30-0005

EAN

4046725357995

label

SIMPLY. CONVINCING.

Ferrules, insulated, 1.5mm², 8 mm, black

General Data

Features	
Construction type	Standard
Nominal cross section	1,5 qmm
Sleeve length	8 mm
Insulated	yes
Halogen free	yes
Colour	Black
Material	Copper
Surface protection	Tinned

Product pictures

Order Data

DEHA no	Type	Item number	EAN	VPE
5150263	2250-30-0005	2250-30-0005	4046725357995	1000 Piece