Datenblatt

RED®

ÜBERZEUGT. EINFACH.

Feuchtraum-Abzweigkasten K 108 leer, 2,5 qmm, IP66, 400 V, 76x76x51 mm, weiß



Leistungsmerkmale

Die RED Kabelabzweigkästen aus 2-Komponenten-Kunststoff sind durch ihre Schlagfestigkeit und Bruchsicherheit für die Installation im Außenbereich bestens geeignet. Sie sind aus witterungs- und UV-beständigem Kunststoff und unabhängig vom RAL-Farbton. Zudem besitzen sie eine hohe Beständigkeit gegenüber pflanzlichen und tierischen Fetten, Mineralöl, Diesel, schwachen Säuren, Lauge sowie Alkohol.
Selbstdichtende, dauerhaft elastische Durchstoßmembrane erlauben eine schnellere Kabeleinführung und ersparen so 30 % Arbeitszeit. Durch das integrierte Gewinde ist auch der Einsatz von Kabelverschraubungen ohne Gegenmutter möglich. Der gewölbte Deckel bietet 10 % mehr Platz im Gehäuse. Unverlierbare Schnellverschluss-Schrauben aus Kunststoff schließen den Kasten mit nur einer Vierteldrehung. (Gilt nicht für die 108er-Serie) Die Befestigung erfolgt über einen Schnellmontagebügel oder innenliegende Öffnungen außerhalb des Dichtbereichs.

DEHA-Nummer

5196626

Artikelnummer

2260-20-0008

EAN

4046725358039

Kennzeichnung

ÜBERZEUGT. EINFACH.

Feuchtraum-Abzweigkasten K 108 leer, 2,5 qmm, IP66, 400 V, 76x76x51 mm, weiß

Allgemeine Daten

Merkmale	
Max. Leiterquerschnitt	2,5 qmm
Form	quadratisch
Montageart	Wand-/Deckenmontage
Länge	76 mm
Breite	76 mm
Tiefe	51 mm
Anreihbar	ja
Anzahl der Einführungen	8
Werkstoff	Kunststoff
Halogenfrei	ja
Oberfläche	unbehandelt
Farbe	weiß
Schutzart (IP)	IP66
Bemessungsisolationsspannung Ui	400 V
Witterungsbeständig	ja

Produktabbildungen

Bestelldaten

DEHA-Nr.	Typ	Artikelnummer	EAN	VPE
5196626	108 leer ws	2260-20-0008	4046725358039	10 Stück

Data Sheet

SIMPLY. CONVINCING.

Humidor junction box K 108 empty, 2,5 qmm, IP66, 400 V, 76x76x51 mm, white



Performance features

The RED cable junction boxes made of 2-component plastic are ideal for outdoor installation due to their impact resistance and breakage resistance. They are made of weather- and UV-resistant plastic and are independent of the RAL color. They are also highly resistant to vegetable and animal fats, mineral oil, diesel, weak acids, alkali and alcohol. Self-sealing, permanently elastic puncture membrane allows cables to be inserted more quickly, saving 30% of working time. The integrated thread also makes it possible to use cable glands without a lock nut. The curved lid offers 10% more space in the case. Captive quick-release plastic screws close the box with just a quarter turn. (Does not apply to the 108 series) It is attached using a quick-mounting bracket or internal openings outside the sealing area.

DEHA number

5196626

Item number

2260-20-0008

EAN

4046725358039

label

Humidor junction box K 108 empty, 2,5 qmm, IP66, 400 V, 76x76x51 mm, white

General Data

Features	
Max. conductor cross section	2,5 qmm
Shape	Square
Mounting method	Wall-/ceiling mounting
Length	76 mm
Width	76 mm
Depth	51 mm
Tackable	yes
Number of inlets	8
Material	Plastic
Halogen free	yes
Surface protection	Untreated
Colour	White
Degree of protection (IP)	IP66
Rated insulation voltage Ui	400 V
Weatherproof	yes

Product pictures

Order Data

DEHA no	Type	Item number	EAN	VPE
5196626	108 leer ws	2260-20-0008	4046725358039	10 Piece