



Kunststoff-Leerrohr biegsam Type 50,  
Klassif.33332, RAL 7037, grau, 750 N / 5cm



4 046725 358084

#### Leistungsmerkmale

Das Kunststoff-Leerrohr der Klassifizierung 33332 ist ein biegsames, hochflexibles Kunststoffpanzer-Leerrohr aus Spezialkunststoff. Das Rohr ist temperaturbeständig von -15 bis +105° Grad Celsius. Weiterhin ist das Rohr flammwidrig und selbstverlöschend sowie korrosionsfest.

#### Die weiteren Produkteigenschaften:

- Druckfestigkeit: mittel, 750 N / 5 cm
- Schlagfestigkeit: mittel, 2,0 kg / 100 mm
- Biegeverhalten: biegsam nach DIN EN 61386-22

#### Der Anwendungsbereich:

Das Kunststoff-Leerrohr ist insbesondere geeignet für Betonverlegung und überall dort, wo erhöhte Temperaturen auftreten.

#### DEHA Nummer

5219271

#### Artikelnummer

2210-20-0005

#### EAN-Nummer

4046725358084

#### Kennzeichnung



#### Zusatzinformation

##### Normen:

DIN EN 61386-1 (VDE 0605-1)  
DIN EN 61386-22 (VDE 0605-22)  
DIN EN 60423


Kunststoff-Leerrohr biegsam Type 50,  
Klassif.33332, RAL 7037, grau, 750 N / 5cm

### Allgemeine Daten

#### Merkmale

|                     |                               |
|---------------------|-------------------------------|
| Druckfestigkeit     | mittel, 750 N / 5cm           |
| Schlagfestigkeit    | mittel, 2,0 kg / 100 mm       |
| Temperaturbeständig | von -15 bis +105°C            |
| Biegeverhalten      | biegsam, nach DIN EN 61386-22 |
| Ø Innen             | 40 mm                         |
| Ø Außen             | 50 mm                         |
| Farbe               | grau                          |
| Ringinhalt          | 25 m                          |
| Gewicht pro Ring    | 5,7 kg                        |
| Biegeradius         | 220 mm                        |
|                     |                               |
|                     |                               |
|                     |                               |
|                     |                               |
|                     |                               |
|                     |                               |
|                     |                               |
|                     |                               |

#### Produktabbildungen



### Bestelldaten

| DEHA-Nummer | Typ              | Art.-Nr.     | EAN-Nr.       | Farbe | VE   |
|-------------|------------------|--------------|---------------|-------|------|
| 5219271     | Ku-Le-Ro 105 M50 | 2210-20-0005 | 4046725358084 | grau  | 50 m |



Plastic empty cable duct flexible type 50,  
classification 33332, RAL 7037, grey, 750 N / 5 cm



4 046725 358084

#### Performance features

The plastic empty cable duct of classification 33332 is a flexible plastic armouring pipe made of special plastic. The tube is temperature resistant from -15 to +105°C. Furthermore, the pipe is flame-resistant and self-extinguishing as well as corrosion-resistant.

#### Other product characteristics:

- Compressive strengt: medium, 750 N / 5 cm
- Impact resistance: medium, 2,0 kg / 100 mm
- Bending properties: flexible according to DIN EN 6138622

#### Application:

The plastic empty cable duct is suitable for concrete laying and wherever elevated temperatures occur.

#### DEHA number

5219271

#### Article number

2210-20-0005

#### EAN number

4046725358084

#### Labels



#### Additional information:

##### Normen:

DIN EN 61386-1 (VDE 0605-1)  
DIN EN 61386-22 (VDE 0605-22)  
DIN EN 60423

Plastic empty cable duct flexible type 50,  
classification 33332, RAL 7037, grey, 750 N / 5 cm

### General data

#### Features

|                        |                                       |
|------------------------|---------------------------------------|
| Compressive strength   | medium, 750 N / 5cm                   |
| Impact resistance      | medium, 2,0 kg / 100 mm               |
| Temperature resistance | from -15 to +105°C                    |
| Bending properties     | flexible according to DIN EN 61386-22 |
| Inner Ø                | 40 mm                                 |
| Outer Ø                | 50 mm                                 |
| Colour                 | grey                                  |
| Ring content           | 25 m                                  |
| Weight per ring        | 5,7 kg                                |
| Bending radius         | 220 mm                                |

#### Product images



### Ordering data

| DEHA number | Typ              | Art.-Nr.     | EAN.-Nr.      | colour | VE |
|-------------|------------------|--------------|---------------|--------|----|
| 5219271     | Ku-Le-Ro 105 M50 | 2210-20-0005 | 4046725358084 | grey   | 25 |