Datenblatt

RED®

ÜBERZEUGT. EINFACH.

Wipptaster beleuchtet FR AP, IP54, 250V, 10A transp. Kalotte



4 046725 358534

Leistungsmerkmale

SPLASH® Wipptaster Schließer mit transparenter Kalotte, LED ist im Lieferumfang enthalten. Mit N-Klemme. Nennspannung 250V, Nennstrom 10A, Schutzart IP54, Schlagfestigkeit IK05. Die Serie SPLASH® besticht durch einen großen Innenraum für eine einfache Verdrahtung. Die Schnellanschlüsse mit Steckklemmen bis 2,5mm² sowie die patentierten asymmetrischen Kabeleinführungsdichtungen erlauben eine schnelle und einfache Installation. Ein Durchverdrahten der Geräte mit 2,5mm² Drähten ist ebenfalls möglich. Zudem besitzt die SPLASH® Produktreihe von RED spezielle Erdungsanschlüsse, die eine Schaltung in einer Gruppe ermöglichen. Die VDE-zertifizierten Pro-dukte sind nach Schlagfestigkeit IK05 geprüft. Die SPLASH® Serie ist in der Farbe Grau erhältlich. Es ist möglich ein Beschriftungsfeld für Schalter und Steckdosen einzusetzen welches optional erhältlich ist. Es kann einfach geöffnet werden und ist durch eine Kunststoffabdeckung gegen Eindringen von Wasser und Feuchtigkeit geschützt. Beleuchtete Schaltervarianten stehen zur Verfügung. Auf nahezu optimale Weise wird SPLASH ®mit Schutz gegen Staub- und Wassereindringen hergestellt um die Schutzklasse IP54 zu garantieren. Nasse Bereiche, harte Bedingungen, Staub, Rauch...: Die neue Produktserie SPLASH® von RED ist diesen Ansprüchen hervorragend gewachsen.

DEHA Nummer

5427448

Artikelnummer

2410-50-0006

EAN-Nummer

4046725358534

Kennzeichnung

Zusatzinformation

RED®

ÜBERZEUGT. EINFACH.

Wipptaster beleuchtet FR AP, IP54, 250V, 10A transp. Kalotte

Allgemeine Daten

Merkmale	
Nennspannung	250 V
Nennstrom	10 A
Farbe	hellgrau
Schutzart	IP54
Schlagfestigkeit	IK05

Produktabbildungen



Bestelldaten

DEHA-Nummer	Typ	Art.-Nr.	EAN-Nr.	VE
5427448	2410-50-0006	2410-50-0006	4046725358534	10/100 Stk.

RED®

ÜBERZEUGT. EINFACH.

Rocker switch FR AP, IP54, 250V, 10A, transparent cap



4 046725 358534

Performance features

SPLASH® rocker button closer with transparent cap, LED is included. With N-clamp. Nominal voltage 250V, rated current 10A, IP54, impact resistance IK05. The SPLASH® series has a large interior for easy wiring. The quick connectors with 2.5 mm² plug-in terminals and the patented asymmetrical cable entry seals allow quick and easy installation. Wiring through the devices with 2.5mm² wires is also possible. In addition, RED's SPLASH® series has special grounding connections that allow a circuit in a group.
The VDE-certified products are tested for impact resistance IK05. The SPLASH® series is available in grey. It is possible to use a labelling field for switches and sockets which is optionally available. It can be easily opened and is protected against ingress of water and moisture by a plastic cover Illuminated switch versions are available. In an almost optimal way, SPLASH® is manufactured with protection against dust and water penetration to guarantee IP54. Wet areas, hard conditions, dust or smoke: The new SPLASH® product range by RED has made excellent use of these requirements.

DEHA number

5427448

Article number

2410-50-0006

EAN number

4046725358534

Labels

RED®

ÜBERZEUGT. EINFACH.

Rocker switch FR AP, IP54, 250V, 10A, transparent cap

General data

Features	
Nominal voltage	250 V
Rated current	10 A
Colour	lightgrey
IP rating	IP54
Impact resistance	IK05

Product pictures



Order data

DEHA-Number	Typ	Art.-Nr.	EAN-Nr.	VE
5427448	2410-50-0006	2410-50-0006	4046725358534	10/100 Pcs.