Datenblatt

RED®

ÜBERZEUGT. EINFACH.

Wippschalter Kreuz FR AP, IP54, 250V, 10A, IK05



4 046725 358589

Leistungsmerkmale

SPLASH® Wippschalter Kreuz, N-Klemme, Nennspannung 250V, Nennstrom 10A, Schutzart IP54, Schlagfestigkeit IK05. Die Serie SPLASH® besticht durch einen großen Innenraum für eine einfache Verdrahtung. Die Schnellanschlüsse mit Steckklemmen bis 2,5mm² sowie die patentierten asymmetrischen Kabeleinführungsdichtungen erlauben eine schnelle und einfache Installation. Ein Durchverdrahten der Geräte mit 2,5mm² Drähten ist ebenfalls möglich. Zudem besitzt die SPLASH® Produktreihe von RED spezielle Erdungsanschlüsse, die eine Schaltung in einer Gruppe ermöglichen. Die VDE-zertifizierten Produkte sind nach Schlagfestigkeit IK05 geprüft. Die SPLASH® Serie ist in der Farbe Grau erhältlich. Es ist möglich ein Beschriftungsfeld für Schalter und Steckdosen einzusetzen welches optional erhältlich ist. Es kann einfach geöffnet werden und ist durch eine Kunststoffabdeckung gegen Eindringen von Wasser und Feuchtigkeit geschützt. Beleuchtete Schaltervarianten stehen zur Verfügung. Auf nahezu optimale Weise wird SPLASH®mit Schutz gegen Staub- und Wasse-reindringen hergestellt um die Schutzklasse IP54 zu garantieren. Nasse Bereiche, harte Bedinungen, Staub, Rauch...: Die neue Produktserie SPLASH® von RED ist diesen Ansprüchen hervorragend gewach-sen.

DEHA Nummer

5427453

Artikelnummer

2410-50-0011

EAN-Nummer

4046725358589


Kennzeichnung

Wippschalter Kreuz FR AP, IP54, 250V, 10A, IK05

Allgemeine Daten

Merkmale	
Nennspannung	250 V
Nennstrom	10 A
Schutzart	IP54
Schlagfestigkeit	IK05
Farbe	hellgrau

Produktabbildungen



Bestelldaten

DEHA-Nummer	Typ	Art.-Nr.	EAN-Nr.	VE
5427453	2410-50-0011	2410-50-0011	4046725358589	10/100 Stk.

Specifications

RED®

ÜBERZEUGT. EINFACH.

Rocker switch cross FR AP, IP54, 250V, 10A, IK05



4 046725 358589

Performance features

SPLASH® rocker switch cross, N-clamp, nominal voltage 250V, rated current 10A, IP54, impact resistance IK05. The SPLASH® series has a large interior for easy wiring. The quick connectors with 2.5 mm² plug-in terminals and the patented asymmetrical cable entry seals allow quick and easy installation. Wiring through the devices with 2.5mm² wires is also possible. In addition, RED's SPLASH® series has special grounding connections that allow a circuit in a group. The VDE-certified products are tested for impact resistance IK05.
The SPLASH® series is available in grey. It is possible to use a labelling field for switches and so-ckets which is optionally available. It can be easily opened and is protected against ingress of water and moisture by a plastic cover. Illuminated switch versions are available. In an almost optimal way, SPLASH® is manufactured with protection against dust and water penetration to guarantee IP54. Wet areas, hard conditions, dust or smoke: The new SPLASH® product series by RED has made excellent use of these requirements.

DEHA number

5427453

Article number

2410-50-0011

EAN number

4046725358589

Labels

RED®


ÜBERZEUGT. EINFACH.

Rocker switch cross FR AP, IP54, 250V, 10A, IK05

General data

Features	
Nominal voltage	250 V
Rated current	10 A
IP rating	IP54
Impact resistance	IK05
Colour	lightgrey

Product pictures



Order data

DEHA-Number	Typ	Art.-Nr.	EAN-Nr.	VE
5427453	2410-50-0011	2410-50-0011	4046725358589	10/100 Pcs.