Datenblatt

RED®

ÜBERZEUGT. EINFACH.

Steckdose Fr AP
IP54, 16A, IK05 m.Klappdeckel



Leistungsmerkmale

SPLASH® Schuko Steckdose mit Sicherheitsschloss (Schließung Nr. 1-5) im Klappdeckel und der Möglichkeit der Beschriftung mit dem entsprechenden Beschriftungsset (2410-50-0027), mit Steckanschluss, 2 P+E, Schloss mit 2 gleichen Schlüsseln, im verschlossenen Zustand nicht aufschaubbar oder zu demontieren, Nennstrom 16A, Schutzart IP54, Schlagfestigkeit IK05. Die Serie SPLASH® besticht durch einen großen Innenraum für eine einfache Verdrahtung. Die Schnellanschlüsse mit Steckklemmen bis 2,5mm² sowie die patentierten asymmetrischen Kabeleinführungsdichtungen erlauben eine schnelle und einfache Installation. Ein Durchverdrahten der Geräte mit 2,5mm² Drähten ist ebenfalls möglich. Zudem besitzt die SPLASH® Produktreihe von RED spezielle Erdungsanschlüsse, die eine Schaltung in einer Gruppe ermöglichen. Die VDE-zertifizierten Produkte sind nach Schlag-festigkeit IK05 geprüft. Die SPLASH® Serie ist in der Farbe Grau erhältlich. Es ist möglich ein Beschriftungsfeld für Schalter und Steckdosen einzusetzen welches optional erhältlich ist. Es kann einfach geöffnet werden und ist durch eine Kunststoffab-deckung gegen Eindringen von Wasser und Feuchtigkeit geschützt. Beleuchtete Schaltervarianten stehen zur Verfügung. Auf nahezu optimale Weise wird SPLASH® mit Schutz gegen Staub- und Wassereindringen hergestellt um die Schutzklasse IP54 zu garantieren. Nasse Bereiche, harte Bedingungen, Staub, Rauch...: Die neue Produktserie SPLASH® von RED ist diesen Ansprüchen hervorragend gewachsen.

DEHA Nummer

5427454 - Schließung 1
5427455 - Schließung 2
5427456 - Schließung 3
5427457 - Schließung 4
5427458 - Schließung 5

Artikelnummer

2410-50-0012
2410-50-0013
2410-50-0014
2410-50-0015
2410-50-0016

EAN-Nummer

4046725358596
4046725358602
4046725358619
4046725358626
4046725358633

Kennzeichnung

Steckdose Fr AP
IP54, 16A, IK05 m.Klappdeckel

Allgemeine Daten

Merkmale	5427454	5427455	5427456
Nennspannung	250 V	250 V	250 V
Nennstrom	16 A	16 A	16 A
Schutzart	IP54	IP54	IP54
Schlagfestigkeit	IK05	IK05	IK05
Farbe	hellgrau	hellgrau	hellgrau
Schließung	1	2	3

Merkmale	5427457	5427458
Nennspannung	250 V	250 V
Nennstrom	16 A	16 A
Schutzart	IP54	IP54
Schlagfestigkeit	IK05	IK05
Farbe	hellgrau	hellgrau
Schließung	4	5

Produktabbildungen



Bestelldaten

DEHA-Nummer	Typ	Art.-Nr.	EAN-Nr.	VE
5427454	2410-50-0012	2410-50-0012	4046725358596	8/80 Stk.
5427455	2410-50-0013	2410-50-0013	4046725358602	8/80 Stk.
5427456	2410-50-0014	2410-50-0014	4046725358619	8/80 Stk.
5427457	2410-50-0015	2410-50-0015	4046725358626	8/80 Stk.
5427458	2410-50-0016	2410-50-0016	4046725358633	8/80 Stk.

Specifications

RED®

ÜBERZEUGT. EINFACH.

Socket FR AP with hinged lid, IP54, 16A, IK05



Performance features

SPLASH® Schuko socket with safety lock (lock no. 1-5) in the hinged lid and the possibility of labelling with the corresponding inscription set (2410-50-0027), with plug-in connection, 2 P + E, lock with 2 identical keys, can't be opened or dismounted when closed and locked, rated current 16A, IP54, impact resistance IK05. The SPLASH® series has a large interior for easy wiring. The quick connectors with 2.5 mm² plug-in terminals and the patented asymmetrical cable entry seals allow quick and easy installation. Wiring through the devices with 2.5mm² wires is also possible.
In addition, RED's SPLASH® series has special grounding connections that allow a circuit in a group. The VDE-certified products are tested for impact resistance IK05. The SPLASH® series is available in grey. It is possible to use a labelling field for switches and sockets which is optionally available. It can be easily opened and is protected against ingress of water and moisture by a plastic cover. Illuminated switch versions are available. In an almost optimal way, SPLASH® is manufactured with protection against dust and water penetration to guarantee IP54. Wet areas, hard conditions, dust or smoke: The new SPLASH® product range from RED has made excellent use of these requirements

DEHA number

5427454 - Saftey lock 1
5427455 - Saftey lock 2
5427456 - Saftey lock 3
5427457 - Saftey lock 4
5427458 - Saftey lock 5

Article number

2410-50-0012
2410-50-0013
2410-50-0014
2410-50-0015
2410-50-0016

EAN number

4046725358596
4046725358602
4046725358619
4046725358626
4046725358633

Labels

RED®

ÜBERZEUGT. EINFACH.

Socket FR AP with hinged lid, IP54, 16A, IK05

General data

Features	5427454	5427455	5427456
Nominal voltage	250 V	250V	250V
Rated current	16 A	16A	16A
IP rating	IP54	IP54	IP54
Impact resistance	IK05	IK05	IK05
Colour	lightgrey	lightgrey	lightgrey
Safety Lock	6	7	8

Merkmale	5427457	5427458
Nominal voltage	250 V	250V
Rated current	16 A	16A
IP rating	IP54	IP54
Impact resistance	IK05	IK05
Colour	lightgrey	lightgrey
Safety Lock	9	10

Product pictures



Bestelldaten

DEHA-Number	Typ	Art.-Nr.	EAN-Nr.	VE
5427454	2410-50-0012	2410-50-0012	4046725358596	8/80 Pcs.
5427455	2410-50-0013	2410-50-0013	4046725358602	8/80 Pcs.
5427456	2410-50-0014	2410-50-0014	4046725358619	8/80 Pcs.
5427457	2410-50-0015	2410-50-0015	4046725358626	8/80 Pcs.
5427458	2410-50-0016	2410-50-0016	4046725358633	8/80 Pcs.