Datenblatt

RED®

ÜBERZEUGT. EINFACH.

Steckdose Fr AP
IP54, 16A, IK05 m.Klappdeckel



Leistungsmerkmale

SPLASH® Schuko Steckdose mit Sicherheitsschloss (Schließung Nr. 6-10) im Klappdeckel und der Möglichkeit der Beschriftung mit dem entsprechenden Beschriftungsset (2410-50-0027), mit Steckanschluss, 2 P+E, Schloss mit 2 gleichen Schlüsseln, im verschlossenen Zustand nicht aufschraubbar oder zu demontieren, Nennstrom 16A, Schutzart IP54, Schlagfestigkeit IK05. Die Serie SPLASH® besticht durch einen großen Innenraum für eine einfache Verdrahtung. Die Schnellanschlüsse mit Steckklemmen bis 2,5mm² sowie die patentierten asymmetrischen Kabeleinführungsdichtungen erlauben eine schnelle und einfache Installation. Ein Durchverdrahten der Geräte mit 2,5mm² Drähten ist ebenfalls möglich. Zudem besitzt die SPLASH® Produktreihe von RED spezielle Erdungsanschlüsse, die eine Schaltung in einer Gruppe ermöglichen. Die VDE-zertifizierten Produkte sind nach Schlag-festigkeit IK05 geprüft. Die SPLASH® Serie ist in der Farbe Grau erhältlich. Es ist möglich ein Beschriftungsfeld für Schalter und Steckdosen einzusetzen welches optional erhältlich ist. Es kann einfach geöffnet werden und ist durch eine Kunststoffabdeckung gegen Eindringen von Wasser und Feuchtigkeit geschützt. Beleuchtete Schaltervarianten stehen zur Verfügung. Auf nahezu optimale Weise wird SPLASH® mit Schutz gegen Staub- und Wassereindringen hergestellt um die Schutzklasse IP54 zu garantieren. Nasse Bereiche, harte Bedingungen, Staub, Rauch...: Die neue Produktserie SPLASH® von RED ist diesen Ansprüchen hervorragend gewach-sen.

DEHA Nummer

5427459 - Schließung 6
5427460 - Schließung 7
5427461 - Schließung 8
5427462 - Schließung 9
5427463 - Schließung 10

Artikelnummer

2410-50-0017
2410-50-0018
2410-50-0019
2410-50-0020
2410-50-0021

EAN-Nummer

4046725358640
4046725358657
4046725358664
4046725358671
4046725358688

Kennzeichnung

Steckdose Fr AP
IP54, 16A, IK05 m.Klappdeckel

Allgemeine Daten

Merkmale	5427459	5427460	5427461
Nennspannung	250 V	250V	250V
Nennstrom	16 A	16A	16A
Schutzart	IP54	IP54	IP54
Schlagfestigkeit	IK05	IK05	IK05
Farbe	hellgrau	hellgrau	hellgrau
Schließung	6	7	8

Merkmale	5427462	5427463
Nennspannung	250 V	250V
Nennstrom	16 A	16A
Schutzart	IP54	IP54
Schlagfestigkeit	IK05	IK05
Farbe	hellgrau	hellgrau
Schließung	9	10

Produktabbildungen



Bestelldaten

DEHA-Nummer	Typ	Art.-Nr.	EAN-Nr.	VE
5427459	2410-50-0017	2410-50-0017	4046725358640	8/80 Stk.
5427460	2410-50-0018	2410-50-0018	4046725358657	8/80 Stk.
5427461	2410-50-0019	2410-50-0019	4046725358664	8/80 Stk.
5427462	2410-50-0020	2410-50-0020	4046725358671	8/80 Stk.
5427463	2410-50-0021	2410-50-0021	4046725358688	8/80 Stk.

Specifications

RED®

ÜBERZEUGT. EINFACH.

Socket FR AP with hinged lid, IP54, 16A, IK05



Performance features

SPLASH® Schuko socket with safety lock (lock no. 6-10) in the hinged lid and the possibility of labelling with the corresponding inscription set (2410-50-0027), with plug-in connection, 2 P + E, lock with 2 identical keys, can't be opened or dismounted when closed and locked, rated current 16A, IP54, impact resistance IK05. The SPLASH® series has a large interior for easy wiring. The quick connectors with 2.5 mm² plug-in terminals and the patented asymmetrical cable entry seals allow quick and easy installation. Wiring through the devices with 2.5mm² wires is also possible. In addition, RED's SPLASH® series has special grounding connections that allow a circuit in a group. The VDE-certified products are tested for impact resistance IK05. The SPLASH® series is available in grey. It is possible to use a labelling field for switches and sockets which is optionally available. It can be easily opened and is protected against ingress of water and moisture by a plastic cover. Illuminated switch versions are available. In an almost optimal way, SPLASH® is manufactured with protection against dust and water penetration to guarantee IP54. Wet areas, hard conditions, dust or smoke: The new SPLASH® product range from RED has made excellent use of these requirements

DEHA number

5427459 · Safety lock 6
5427460 · Safety lock 7
5427461 · Safety lock 8
5427462 · Safety lock 9
5427463 · Safety lock 10

Article number

2410-50-0017
2410-50-0018
2410-50-0019
2410-50-0020
2410-50-0021

EAN number

4046725358640
4046725358657
4046725358664
4046725358671
4046725358688

Labels

RED®

ÜBERZEUGT. EINFACH.

Socket FR AP with hinged lid, IP54, 16A, IK05

General data

Features	5427459	5427460	5427461
Nominal voltage	250 V	250V	250V
Rated current	16 A	16A	16A
IP rating	IP54	IP54	IP54
Impact resistance	IK05	IK05	IK05
Colour	lightgrey	lightgrey	lightgrey
Safety Lock	6	7	8

Merkmale	5427462	5427463
Nominal voltage	250 V	250V
Rated current	16 A	16A
IP rating	IP54	IP54
Impact resistance	IK05	IK05
Colour	lightgrey	lightgrey
Safety Lock	9	10

Product pictures



Bestelldaten

DEHA-Number	Typ	Art.-Nr.	EAN-Nr.	VE
5427459	2410-50-0017	2410-50-0017	4046725358640	8/80 Pcs.
5427460	2410-50-0018	2410-50-0018	4046725358657	8/80 Pcs.
5427461	2410-50-0019	2410-50-0019	4046725358664	8/80 Pcs.
5427462	2410-50-0020	2410-50-0020	4046725358671	8/80 Pcs.
5427463	2410-50-0021	2410-50-0021	4046725358688	8/80 Pcs.