Datenblatt

ÜBERZEUGT. EINFACH.

# Schuko Steckdose FR AP 2-fach, IP54 waagrecht

4 046725 358725

## Leistungsmerkmale

SPLASH® Schuko Steckdose 2fach, für waag-rechte Montage, Steckanschluss, vorverdrahtet mit 2,5qmm flexibel, mit Klappdeckeln, 2 P+E, Nennspannung 250V, Nennstrom 16A, Schutzart IP54, Schlagfestigkeit IK05. Die Serie SPLASH® besticht durch einen großen Innenraum für eine einfache Verdrahtung. Die Schnellanschlüsse mit Steckklemmen bis 2,5mm² sowie die patentierten asymmetrischen Kabeleinführungsdichtungen er-lauben eine schnelle und einfache Installation. Ein Durchverdrahten der Geräte mit 2,5mm² Drähten ist ebenfalls möglich. Zudem besitzt die SPLASH® Produktreihe von RED spezielle Erdungsanschlüsse, die eine Schaltung in einer Gruppe ermöglichen. Die VDE-zertifizierten Produkte sind nach Schlag-festigkeit IK05 geprüft. Die SPLASH® Serie ist in der Farbe Grau erhältlich. Es ist möglich ein Beschriftungsfeld für Schalter und Steckdosen einzusetzen welches optional erhältlich ist. Es kann einfach geöffnet werden und ist durch eine Kunststoffabdeckung gegen Eindringen von Wasser und Feuchtigkeit geschützt. Beleuchtete Schaltervarianten stehen zur Verfügung. Auf nahezu optimale Weise wird SPLASH® mit Schutz gegen Staub- und Wassereindringen hergestellt um die Schutzklasse IP54 zu garantieren. Nasse Bereiche, harte Bedingungen, Staub, Rauch...: Die neue Produktserie SPLASH® von RED ist diesen Ansprüchen hervorragend gewach-sen.

## DEHA Nummer

5427467

## Artikelnummer

2410-50-0025

## EAN-Nummer

4046725358725

## Kennzeichnung

ÜBERZEUGT. EINFACH.

# Schuko Steckdose FR AP 2-fach, IP54 waagrecht



## Allgemeine Daten

| Merkmale | |
|---|---|
| Nennspannung | 250 V |
| Nennstrom | 16 A |
| Schutzart | IP54 |
| Schlagfestigkeit | IK05 |
| Farbe | hellgrau |

### Produktabbildungen

## Bestelldaten

| DEHA-Nummer | Typ | Art.-Nr. | EAN-Nr. | VE |
|---|---|---|---|---|
| 5427467 | 2410-50-0025 | 2410-50-0025 | 4046725358725 | 10/60 Stk. |

RED®

ÜBERZEUGT. EINFACH.

# Schuko socket FR AP 2-fold, IP54 horizontal

4 046725 358725

## Performance features

SPLASH® Schuko socket 2-fold, for horizontal mounting, plug connection, pre-wired with 2,5qmm flexible, with hinged covers, 2 P + E, nominal voltage 250V, rated current 16A, IP54, impact resistance IK05. The SPLASH® series has a large interior for easy wiring. The quick connectors with 2.5 mm² plug-in terminals and the patented asymmetrical cable entry seals allow quick and easy installation. Wiring through the devices with 2.5mm² wires is also possible.
In addition, RED's SPLASH® series has special grounding connections that allow a circuit in a group. The VDE-certified products are tested for impact resistance IK05. The SPLASH® series is available in grey. It is possible to use a labelling field for switches and sockets which is optionally available. It can be easily opened and is protected against ingress of water and moisture by a plastic cove. Illuminated switch versions are available. In an almost optimal way, SPLASH® is manufactured with protection against dust and water penetration to guarantee IP54. Wet areas, hard conditions, dust or smoke: The new SPLASH® product series from RED has made excellent use of these requirements.

## DEHA number

5427467

## Article number

2410-50-0025

## EAN number

4046725358725

## Labels

ÜBERZEUGT. EINFACH.

# Schuko socket FR AP 2-fold, IP54 horizontal



## General data

| Features | |
|---|---|
| Nominal voltage | 250 V |
| Rated current | 16 A |
| IP rating | IP54 |
| Impact resistance | IK05 |
| Colour | lightgrey |

### Product pictures

## Bestelldaten

| DEHA-Number | Typ | Art.-Nr. | EAN-Nr. | VE |
|---|---|---|---|---|
| 5427467 | 2410-50-0025 | 2410-50-0025 | 4046725358725 | 10/60 Pcs. |