Datenblatt

ÜBERZEUGT. EINFACH.

Schuko Steckdose FR AP 3-fach, IP54 waagrecht

4 046725 358770

Leistungsmerkmale

SPLASH® Schuko Steckdose 3fach, für waag-rechte Montage, Steckanschluss, vorverdrahtet mit 2,5qmm flexibel, mit Klappdeckeln, 2 P+E, Nennspannung 250V, Nennstrom 16A, Schutzart IP54, Schlagfestigkeit IK05. Die Serie SPLASH® besticht durch einen großen Innenraum für eine einfache Verdrahtung. Die Schnellanschlüsse mit Steckklemmen bis 2,5mm² sowie die patentierten asymmetrischen Kabeleinführungsdichtungen erlauben eine schnelle und einfache Installation. Ein Durchverdrahten der Geräte mit 2,5mm² Drähten ist ebenfalls möglich. Zudem besitzt die SPLASH® Produktreihe von RED spezielle Erdungsanschlüsse, die eine Schaltung in einer Gruppe ermöglichen. Die VDE-zertifizierten Produkte sind nach Schlagfestigkeit IK05 geprüft. Die SPLASH® Serie ist in der Farbe Grau erhältlich. Es ist möglich ein Beschriftungsfeld für Schalter und Steckdosen einzusetzen welches optional erhältlich ist. Es kann einfach geöffnet werden und ist durch eine Kunststoffabdeckung gegen Eindringen von Wasser und Feuchtigkeit geschützt. Beleuchtete Schaltervarianten stehen zur Verfügung. Auf nahezu optimale Weise wird SPLASH® mit Schutz gegen Staub- und Wassereindringen hergestellt um die Schutzklasse IP54 zu garantieren. Nasse Bereiche, harte Bedingungen, Staub, Rauch...: Die neue Produktserie SPLASH® von RED ist diesen Ansprüchen hervorragend gewachsen.

DEHA Nummer

5427472

Artikelnummer

2410-50-0030

EAN-Nummer

4046725358770

Kennzeichnung

ÜBERZEUGT. EINFACH.

Schuko Steckdose FR AP 3-fach, IP54 waagrecht

Allgemeine Daten

Merkmale	
Nennspannung	250 V
Nennstrom	16 A
Schutzart	IP54
Schlagfestigkeit	IK05
Farbe	hellgrau

Produktabbildungen

Bestelldaten

DEHA-Nummer	Typ	Art.-Nr.	EAN-Nr.	VE
5427472	2410-50-0030	2410-50-0030	4046725358770	24 Stk.

ÜBERZEUGT. EINFACH.

Schuko socket FR AP 3-fach, IP54 horizontal

4 046725 358770

Performance features

SPLASH® Schuko socket 3-fold, for horizontal mouning, plug connection, pre-wired with 2,5qmm flexible, with hinged covers, 2 P + E, nominal voltage 250V, rated current 16A, IP54, impact resistance IK05. The SPLASH® series has a large interior for easy wiring. The quick connectors with 2.5 mm² plug-in terminals and the patented asymmetrical cable entry seals allow quick and easy installation. Wiring through the devices with 2.5mm² wires is also possible. In addition, RED's SPLASH® series has special grounding connections that allow a cir-cuit in a group. The VDE-certified products are tes-ted for impact resistance IK05. The SPLASH® series is available in grey. It is possible to use a labelling field for switches and sockets which is optionally available. It can be easily opened and is protected against ingress of water and moisture by a plastic cover. Illuminated switch versions are available. In an almost optimal way, SPLASH® is manufactured with protection against dust and water penetration to guarantee IP54. Wet areas, hard conditions, dust or smoke: The new SPLASH® product range from RED has made excellent use of these requirements

DEHA number

5427472

Article number

2410-50-0030

EAN number

4046725358770

Labels

ÜBERZEUGT. EINFACH.

Schuko socket FR AP 3-fach, IP54 horizontal

General data

Features	
Nominal voltage	250 V
Rated current	16 A
IP rating	IP54
Impact resistance	IK05
Colour	lightgrey

Product pictures

Order data

DEHA-Number	Typ	Art.-Nr.	EAN-Nr.	VE
5427472	2410-50-0030	2410-50-0030	4046725358770	24 Pcs.