Datenblatt

RED®

ÜBERZEUGT. EINFACH.

Schlag-/Nageldübel BFM-SND FK 6x40, flacher Kragen, Zylinderkopf, Kreuzschlitz, Polyamid PA 6



4 046725 359357

Leistungsmerkmale

Der RED Schlag-/Nageldübel ist eine perfekte Kombination aus Funktionalität und einer sehr guten Qualität. Durch die präzise Führung des Nagels kann man den Schlag-/Nageldübel einfach einschlagen. Der Dübel ist aus Nylon und somit reißfest sowie hitze- und kältebeständig.

Der verzinkte Nagel sichert eine hohe Korrosionsbeständigkeit. Der Schlag-/Nageldübel besitzt einen schlaggeschützten Kreuzschlitz und schützt somit vor einer Beschädigung des Antriebs.
Die Einschlagsicherung verhindert ein vorzeitiges Spreizen.

Technische Daten

- Material Dübel/Nagel: Polyamid PA 6/Stahl, die Oberfläche des Nagels ist galvanisch verzinkt
- Zugfestigkeit: 500–700 N/mm²
- Halogenfrei

DEHA-Nummer

5836492

Artikelnummer

2110-20-0007

EAN

4046725359357

Kennzeichnung

Schlag-/Nageldübel BFM-SND FK 6x40, flacher Kragen, Zylinderkopf, Kreuzschlitz, Polyamid PA 6

Allgemeine Daten

Merkmale	
Bohrlochdurchmesser	6 mm
Befestigungsstärke	30 mm
Länge	40 mm
Werkstoff Dübel	Kunststoff
Schraubsystem	Pozidriv PZ
Schraubnagel mitgeliefert	ja
Stiftform	Nagelschraube
Farbe	Natur

Produktabbildungen

Bestelldaten

DEHA-Nr.	Typ	Artikelnummer	EAN	VPE
5836492	BFM-SND BK 6x40 natur	2110-20-0007	4046725359357	200 Stück

Data Sheet

RED®

SIMPLY. CONVINCING.

Impact/nail anchor BFM-SND FK 6x40, flat collar, cylinder head, Phillips head, polyamide PA 6



4 046725 359357

Performance features

The RED impact/nail anchor is a perfect combination of functionality and very good quality. Thanks to the precise guidance of the nail, you can simply hammer in the impact/nail dowel. The dowel is made of nylon and is therefore tear-resistant and resistant to heat and cold.

The galvanized nail ensures high corrosion resistance. The impact/nail anchor has an impact-protected cross slot and thus protects against damage to the drive. The impact protection prevents premature spreading.

Technical specifications

- Material dowel/nail: Polyamide PA 6/steel, the surface of the nail is galvanized
- Tensile strength: 500-700 N/mm²
- Halogen free

DEHA number

5836492

Item number

2110-20-0007

EAN

4046725359357

label

Impact/nail anchor BFM-SND FK 6x40, flat collar, cylinder head, Phillips head, polyamide PA 6

General Data

Features	
Drill hole diameter	6 mm
Mounting thickness	30 mm
Length	40 mm
Material plug	Plastic
Screwing system	Pozidriv PZ
Screw nail included	yes
Pin shape	Nail screw
Colour	Natur

Product pictures

Order Data

DEHA no	Type	Item number	EAN	VPE
5836492	BFM-SND BK 6x40 natur	2110-20-0007	4046725359357	200 Piece