




LED Linearleuchte LIXX[®] 9 W,
900 lm, 3000 K, 580 mm



Leistungsmerkmale

Die LIXX[®] Serie ist eine vielseitige LED-Linearleuchte mit besonders schmaler Bauform. Das Gehäuse besteht aus einem Aluminiumprofil mit einer PC Kunststoffabdeckung. Die Leuchten der LIXX[®] Serie sind in vier Längen (580, 880, 1180 und 1480 mm) und zwei Farbtemperaturen (3000 K und 4000 K) erhältlich.

Die LIXX[®] Linearleuchten sind für Wand-, Decken- und Anbaumontage geeignet. Bis zu 20 LIXX[®] Leuchten können über den mitgelieferten Verbindungsadapter zusammengesteckt und an einem Anschluss betrieben werden. Zusätzlich ist ein separater Ein-/Ausschalter erhältlich, welcher maximal 8 LIXX[®] Leuchten schalten kann. Die robuste Bauweise sichert auch bei diesen Produkten eine beachtliche Nennlebensdauer von 50.000 Stunden.

Lieferumfang:

25 cm Anschlussleitung, Verbindungsadapter,
2x Montageklammern mit Dübel und Schraube

DEHA-Nummer

5863675

Artikelnummer

5610-40-0001

EAN

4046725360018

Kennzeichnung



ÜBERZEUGT. EINFACH.

LED Linearleuchte LIXX® 9 W,
900 lm, 3000 K, 580 mm

Allgemeine Daten

Merkmale	
Geeignet für Wandmontage	ja
Geeignet für Deckenmontage	ja
Geeignet für Anbaumontage	ja
Leuchtmittel	LED nicht austauschbar
Mit Leuchtmittel	ja
Fassung	ohne
Werkstoff des Gehäuses	Aluminium
Gehäusefarbe	Aluminium
Werkstoff der Abdeckung	PC
Ausführung des Rasters	ohne
Spannungsart	AC
Nennspannung	90 - 265 V AC 50/60 Hz
Betriebsgerät	nicht erforderlich
Mit Betriebsgerät	ja
Lichtverteilung	symmetrisch
Ausstrahlungswinkel	freistrahlend/diffus 120°
Lichtaustritt	direkt
Energieeffizienzklasse des fest eingebauten Leuchtmittels	F
Bemessungslebensdauer L70/B10 bei 25 °C	50000 h
Schutzart (IP)	IP20
Schutzklasse	I
Bemessungsumgebungstemperatur nach IEC62722-2-1	-10 - 40 °C
Max. Systemleistung	9 W
Bemessungslichtstrom nach IEC 62722-2-1	900 lm
Lichtfarbe	weiß
Farbtemperatur	3000 K
Farbwiedergabeindex CRI	80-89
Breite	25 mm
Höhe/Tiefe	28 mm
Länge	580 mm

Bestelldaten

DEHA-Nr.	Typ	Artikelnummer	EAN	VPE
5863675	LED LIXX® T5 3000K 9W 580mm alu	5610-40-0001	4046725360018	1 Stück

Technische Änderungen vorbehalten

Verpackungsregisternr. DE3513737456573; WEEE-Reg.-Nr. DE 89717721


DEHA Elektrohandelsgesellschaft mbH & Co.KG, Weilimdorfer Str. 74/2, 70839 Gerlingen, Deutschland

www.deha.de

www.wir-sind-red.de



LED linear light LIXX[®] 9 W,
900 lm, 3000 K, 580 mm



Performance features

The LIXX[®] series is a versatile LED linear light with a particularly narrow design. The housing consists of an aluminum profile with a PC plastic cover. The LIXX[®] series lights are available in four lengths (580, 880, 1180 and 1480 mm) and two color temperatures (3000 K and 4000 K).

The LIXX[®] linear lights are suitable for wall, ceiling and surface-mounting. Up to 20 LIXX[®] lights can be plugged together using the included connection adapter and operated on one connection. A separate on/off switch is also available, which can switch a maximum of 8 LIXX[®] lights. The robust construction also ensures a remarkable nominal service life of 50,000 hours for these products.

Scope of delivery:

25 cm connection cable, connection adapter,
2x mounting brackets with dowels and screws

DEHA number

5863675

Item number

5610-40-0001

EAN

4046725360018

label

General Data

Features	
Suitable for wall mounting	yes
Suitable for ceiling mounting	yes
Suitable for surface mounting	yes
Lamp type	LED not exchangeable
With light source	yes
Lamp holder	None
Material housing	Aluminium
Colour housing	Aluminium
Material cover	PC
Type of grid	None
Voltage type	AC
Nominal voltage	90 - 265 V AC 50/60 Hz
Type of control gear	Not required
Control gear included	yes
Light sharing	Symmetric
Beam angle	unshielded/diffuse 120°
Light outlet	Direct
Energy efficiency class of the built-in lamp	F
Rated life time L70/B10 at 25 °C	50000 h
Degree of protection (IP)	IP20
Protection class	I
Rated ambient temperature acc. IEC62722-2-1	-10 - 40 °C
Max. system power	9 W
Rated luminous flux acc. IEC 62722-2-1	900 lm
Colour of light	White
Colour temperature	3000 K
Colour rendering index CRI	80-89
Width	25 mm
Height/depth	28 mm
Length	580 mm

Order Data

DEHA no	Type	Item number	EAN	VPE
5863675	LED LIXX [®] T5 3000K 9W 580mm alu	5610-40-0001	4046725360018	1 Piece