Datenblatt

RED®

ÜBERZEUGT. EINFACH.

Zwillingsaderendhülse, isoliert, 2x 0,75 mm², 8 mm, grau



4 046725 360308

Leistungsmerkmale

Die isolierten Zwillingsaderendhülsen garantieren eine optimale elektrische Verbindung zwischen Leiter und Kabelklemme sowie eine einfache Montage. Gratfreie Ausführung in Länge 8–14 mm, mit Aufweitung, zur einfachsten und spleißfreien Kabeleinführung. Material: Hülse aus Kupfer gefertigt, in galvanisch verzinnter Ausführung für höchstmöglichen Korrosionsschutz.
Die Isolation aus Polypropylen garantiert eine hohe Lebensdauer und Bruchsicherheit. Extreme Temperaturbeständigkeit für Schaltschrankumgebungsbedingungen bis **105 °C**. Ausführung der Farbgebung und Abmessungen gemäß DIN 46228 Teil 4.

DEHA-Nummer

5932773

Artikelnummer

2250-30-0026

EAN

4046725360308

Kennzeichnung

RED®

ÜBERZEUGT. EINFACH.

Zwillingsaderendhülse, isoliert, 2x 0,75 mm², 8 mm, grau

Allgemeine Daten

Merkmale	
Bauform	Zwillings-Aderendhülse
Nennquerschnitt	0,75 qmm
Hülsenlänge	8 mm
Isoliert	ja
Halogenfrei	ja
Farbe	grau
Werkstoff	Kupfer
Oberfläche	verzinnt

Produktabbildungen

Bestelldaten

DEHA-Nr.	Typ	Artikelnummer	EAN	VPE
5932773	2250-30-0026	2250-30-0026	4046725360308	1000 Stück

Data Sheet

RED®

SIMPLY. CONVINCING.

Twin ferrule, insulated, 2x 0.75 mm², 8 mm, grey



4 046725 360308

Performance features

The insulated twin wire end sleeves guarantee an optimal electrical connection between conductor and cable clamp as well as easy installation. Burr-free version in length 8–14 mm, with expansion, for the simplest and splice-free cable entry. Material: Sleeve made of copper, in a galvanized tin-plated version for the highest possible corrosion protection.
The polypropylene insulation guarantees a long service life and resistance to breakage. Extreme temperature resistance for control cabinet ambient conditions up to **105 °C**. Coloring and dimensions in accordance with DIN 46228 Part 4.

DEHA number

5932773

Item number

2250-30-0026

EAN

4046725360308

label

Twin ferrule, insulated, 2x 0.75 mm², 8 mm, grey

General Data

Features	
Construction type	Twin cable end sleeve
Nominal cross section	0,75 qmm
Sleeve length	8 mm
Insulated	yes
Halogen free	yes
Colour	Grey
Material	Copper
Surface protection	Tinned

Product pictures

Order Data

DEHA no	Type	Item number	EAN	VPE
5932773	2250-30-0026	2250-30-0026	4046725360308	1000 Piece