Datenblatt

RED®

ÜBERZEUGT. EINFACH.

Feuchtraumleuchte SPLIXX® für T8-LED-Röhren 158, 1x 1500 mm, IP66



4 046725 360421

Leistungsmerkmale

Die RED Feuchtraumleuchte SPLIXX® ist eine preislich sehr attraktive und wirtschaftliche Lösung für T8-LED-Röhren im Netzspannungsbetrieb; Einsatz im Innen- und überdachten Außenbereich.

Technische Daten

- Werkzeugloser Zugang zum Geräteträger
- Stirnseitige Kabeleinführung
- Verschlussclips und Deckenbefestigung aus Edelstahl
- Für netzspannungstaugliche LED-Röhren KVG/VVG oder Universal-LED-Tube 1500 mm

5-polige Durchgangsverdrahtung ist als Zubehör erhältlich. DEHA-Nr. **6001863**

Leuchtmittel-Empfehlung:

LEDVANCE®	DEHA-Nr.
LED TUBE T8 EM UO S 1500 22,2 W 830	6981657
LED TUBE T8 EM UO S 1500 22,1 W 840	6981658
LED TUBE T8 EM UO S 1500 22,1 W 865	6981660
LED TUBE T8 EM V 1500 18,3 W 830	6981322
LED TUBE T8 EM V 1500 18,3 W 865	6981324
ST8AUO 23.1 W/830 220–240 V EM	6625838
ST8AUO 23.1 W/840 220–240 V EM	6625839
ST8AUO 23.1 W/865 220–240 V EM	6625840
ST8A 20.6 W/840 220–240 V EM	6625845
ST8A 20.6 W/865 220–240 V EM	6625846
ST8V 18.3 W/830 220–240 V EM	6625853
ST8V 18.3 W/840 220–240 V EM	6625854
ST8V 18.3 W/865 220–240 V EM	6625855

DEHA-Nummer

5935842


Artikelnummer

5640-30-0003

EAN

4046725360421

Zubehör



Feuchtraumleuchte SPLIXX® für T8-LED-Röhren 158, 1x 1500 mm, IP66

Allgemeine Daten

Merkmale	
Geeignet für Wandmontage	ja
Geeignet für Pendelaufhängung	ja
Geeignet für Deckenmontage	ja
Geeignet für Anbaumontage	ja
Leuchtmittel	LED austauschbar
Geeignet für Leuchtmittelanzahl	1
Fassung	G13
Werkstoff des Gehäuses	Polycarbonat
Gehäusefarbe	grau RAL 7035
Werkstoff der Abdeckung	Polycarbonat
Nennspannung	220 - 240 V AC 50/60 Hz
Betriebsgerät	nicht erforderlich
Lichtverteilung	symmetrisch
Ausstrahlungswinkel	breitstrahlend 41-80°
Lichtaustritt	direkt
Schutzart (IP)	IP66
Schlagfestigkeit	IK08
Schutzklasse	I
Breite	101 mm
Höhe/Tiefe	101 mm
Länge	1573 mm
Glühdrahtprüfung nach IEC 60695-2-11	850 °C

Bestelldaten

DEHA-Nr.	Typ	Artikelnummer	EAN	VPE
5935842	FR-Leuchte SPLIXX® für T8-LED-Röhren 158	5640-30-0003	4046725360421	1 Stück

Data Sheet

RED®
SIMPLY. CONVINCING.

SPLIXX® moisture-proof luminaire for T8 LED tubes 158, 1x 1500 mm, IP66



4 046725 360421

Performance features

The RED SPLIXX® moisture-proof luminaire is a very attractively priced and economical solution for T8 LED tubes in mains voltage operation; Indoor and covered outdoor use.

Technical specifications

- Tool-free access to the implement carrier
- Front cable entry
- Stainless steel locking clips and ceiling mount
- For mains voltage compatible LED tubes CCG/LLC or universal LED tube 1500 mm

5-pin through-wiring is available as an accessory.
DEHA no. **6001863**

Recommended lamps:


LEDVANCE®	DEHA-No.
LED TUBE T8 EM UO S 1500 22,2 W 830	6981657
LED TUBE T8 EM UO S 1500 22,1 W 840	6981658
LED TUBE T8 EM UO S 1500 22,1 W 865	6981660
LED TUBE T8 EM V 1500 18,3 W 830	6981322
LED TUBE T8 EM V 1500 18,3 W 865	6981324
ST8AUO 23.1 W/830 220–240 V EM	6625838
ST8AUO 23.1 W/840 220–240 V EM	6625839
ST8AUO 23.1 W/865 220–240 V EM	6625840
ST8A 20.6 W/840 220–240 V EM	6625845
ST8A 20.6 W/865 220–240 V EM	6625846
ST8V 18.3 W/830 220–240 V EM	6625853
ST8V 18.3 W/840 220–240 V EM	6625854
ST8V 18.3 W/865 220–240 V EM	6625855

DEHA number
5935842

Item number
5640-30-0003

EAN
4046725360421

Accesories



SIMPLY. CONVINCING.

SPLIXX® moisture-proof luminaire for T8 LED tubes 158, 1x 1500 mm, IP66

General Data

Features	
Suitable for wall mounting	yes
Suitable for suspended mounting	yes
Suitable for ceiling mounting	yes
Suitable for surface mounting	yes
Lamp type	LED exchangeable
Suitable for number of lamps	1
Lamp holder	G13
Material housing	Polycarbonate
Colour housing	grau RAL 7035
Material cover	Polycarbonate
Nominal voltage	220 - 240 V AC 50/60 Hz
Type of control gear	Not required
Light sharing	Symmetric
Beam angle	Wide beam 41-80°
Light outlet	Direct
Degree of protection (IP)	IP66
Impact strength	IK08
Protection class	I
Width	101 mm
Height/depth	101 mm
Length	1573 mm
Filament test according to IEC 60695-2-11	850 °C

Order Data

DEHA no	Type	Item number	EAN	VPE
5935842	FR-Leuchte SPLIXX® für T8-LED-Röhre 158	5640-30-0003	4046725360421	1 Piece