Datenblatt

RED®

ÜBERZEUGT. EINFACH.

Feuchtraumleuchte SPLIXX® konventionell 158, 1x 1500 mm, IP66, EVG



4 046725 360445

Leistungsmerkmale

Die RED Feuchtraumleuchte SPLIXX® ist bestens für konventionelle Leuchtstofflampen T8 mit schaltbarem, elektronischem Vorschaltgerät geeignet, Einsatz im Innen- und überdachten Außenraum.

Technische Daten

- Werkzeugloser Zugang zum Geräteträger
- Stirnseitige Kabeleinführung
- Verschlussclips und Deckenbefestigung aus Edelstahl
- Für Bestückung T8 (T26) 58 W
- 5-polige Durchgangsverdrahtung als Zubehör DEHA-Nr.: 6001863

DEHA-Nummer

5935844


Artikelnummer

5420-45-0001

EAN

4046725360445

Zubehör



Feuchtraumleuchte SPLIXX® konventionell 158, 1x 1500 mm, IP66, EVG

Allgemeine Daten

Merkmale	
Geeignet für Wandmontage	ja
Geeignet für Pendelaufhängung	ja
Geeignet für Deckenmontage	ja
Leuchtmittel	Leuchtstofflampe D=26 mm
Geeignet für Anbaumontage	ja
Geeignet für Leuchtmittelanzahl	1
Fassung	G13
Werkstoff des Gehäuses	Polycarbonat
Gehäusefarbe	grau RAL 7035
Werkstoff der Abdeckung	Polycarbonat
Nennspannung	220 - 240 V AC 50/60 Hz
Betriebsgerät	EVG Standard
Mit Betriebsgerät	ja
Lichtverteilung	symmetrisch
Ausstrahlungswinkel	breitstrahlend 41-80°
Lichtaustritt	direkt
Schutzart (IP)	IP66
Schlagfestigkeit	IK08
Schutzklasse	I
Leuchte mit begrenzter Oberflächentemperatur „D-Zeichen“	ja
Breite	101 mm
Höhe/Tiefe	101 mm
Länge	1573 mm
Glühdrahtprüfung nach IEC 60695-2-11	850 °C

Bestelldaten

DEHA-Nr.	Typ	Artikelnummer	EAN	VPE
5935844	FR-SPLIXX® 158 EVG	5420-45-0001	4046725360445	1 Stück

Data Sheet

RED®
SIMPLY. CONVINCING.

Moisture-proof light SPLIXX® conventional 158, 1x 1500 mm, IP66, EVG



4 046725 360445

Performance features

The RED SPLIXX® moisture-proof luminaire is ideally suited for conventional T8 fluorescent lamps with switchable electronic ballasts, for use indoors and in covered outdoor areas.

Technical specifications

- Tool-free access to the implement carrier
- Front cable entry
- Stainless steel locking clips and ceiling mount
- For configuration T8 (T26) 58 W
- 5-pin through-wiring as an accessory
  DEHA no.: 6001863

DEHA number

5935844


Item number

5420-45-0001

EAN

4046725360445

Accesories



SIMPLY. CONVINCING.

Moisture-proof light SPLIXX® conventional 158, 1x 1500 mm, IP66, EVG

General Data

Features	
Suitable for wall mounting	yes
Suitable for suspended mounting	yes
Suitable for ceiling mounting	yes
Lamp type	Fluorescent lamp D=26 mm
Suitable for surface mounting	yes
Suitable for number of lamps	1
Lamp holder	G13
Material housing	Polycarbonate
Colour housing	grau RAL 7035
Material cover	Polycarbonate
Nominal voltage	220 - 240 V AC 50/60 Hz
Type of control gear	Electronic ballast standard
Control gear included	yes
Light sharing	Symmetric
Beam angle	Wide beam 41-80°
Light outlet	Direct
Degree of protection (IP)	IP66
Impact strength	IK08
Protection class	I
Luminaire with limited surface temperature, sign „D“	yes
Width	101 mm
Height/depth	101 mm
Length	1573 mm
Filament test according to IEC 60695-2-11	850 °C

Order Data

DEHA no	Type	Item number	EAN	VPE
5935844	FR-SPLIXX® 158 EVG	5420-45-0001	4046725360445	1 Piece