Datenblatt

RED®

ÜBERZEUGT. EINFACH.

Feuchtraumleuchte SPLIXX® konventionell 258, 2x 1500 mm, IP66, EVG



4 046725 360452

Leistungsmerkmale

Die RED Feuchtraumleuchte SPLIXX® ist bestens für konventionelle Leuchtstofflampen T8 mit schaltbarem, elektronischem Vorschaltgerät geeignet, Einsatz im Innen- und überdachten Außenraum.

Technische Daten

- Werkzeugloser Zugang zum Geräteträger
- Stirnseitige Kabeleinführung
- Verschlussclips und Deckenbefestigung aus Edelstahl
- Für Bestückung T8 (T26) 58 W
- 5-polige Durchgangsverdrahtung als Zubehör DEHA-Nr.: 6001863

DEHA-Nummer

5935845


Artikelnummer

5420-45-0002

EAN

4046725360452

Zubehör



Feuchtraumleuchte SPLIXX® konventionell 258, 2x 1500 mm, IP66, EVG

Allgemeine Daten

Merkmale	
Geeignet für Wandmontage	ja
Geeignet für Pendelaufhängung	ja
Geeignet für Deckenmontage	ja
Geeignet für Anbaumontage	ja
Leuchtmittel	Leuchtstofflampe D=26 mm
Geeignet für Leuchtmittelanzahl	2
Fassung	G13
Werkstoff des Gehäuses	Polycarbonat
Gehäusefarbe	grau RAL 7035
Werkstoff der Abdeckung	Polycarbonat
Nennspannung	220 - 240 V AC 50/60 Hz
Betriebsgerät	EVG Standard
Mit Betriebsgerät	ja
Lichtverteilung	symmetrisch
Ausstrahlungswinkel	breitstrahlend 41-80°
Lichtaustritt	direkt
Schutzart (IP)	IP66
Schlagfestigkeit	IK08
Schutzklasse	I
Leuchte mit begrenzter Oberflächentemperatur „D-Zeichen“	ja
Breite	145 mm
Höhe/Tiefe	101 mm
Länge	1573 mm
Glühdrahtprüfung nach IEC 60695-2-11	850 °C

Bestelldaten

DEHA-Nr.	Typ	Artikelnummer	EAN	VPE
5935845	FR-Anbauleuchte SPLIXX® 258 EVG	5420-45-0002	4046725360452	1 Stück

Data Sheet

RED®

SIMPLY. CONVINCING.

Moisture-proof light SPLIXX® conventionel 258, 2x 1500 mm, IP66, EVG



4 046725 360452

Performance features

The RED SPLIXX® moisture-proof luminaire is ideally suited for conventional T8 fluorescent lamps with switchable electronic ballasts, for use indoors and in covered outdoor areas.

Technical specifications

- Tool-free access to the implement carrier
- Front cable entry
- Stainless steel locking clips and ceiling mount
- For configuration T8 (T26) 58 W
- 5-pin through-wiring as an accessory
  DEHA no.: 6001863

DEHA number

5935845


Item number

5420-45-0002

EAN

4046725360452

Accesories



Moisture-proof light SPLIXX® conventionel 258, 2x 1500 mm, IP66, EVG

General Data

Features	
Suitable for wall mounting	yes
Suitable for suspended mounting	yes
Suitable for ceiling mounting	yes
Suitable for surface mounting	yes
Lamp type	Fluorescent lamp D=26 mm
Suitable for number of lamps	2
Lamp holder	G13
Material housing	Polycarbonate
Colour housing	grau RAL 7035
Material cover	Polycarbonate
Nominal voltage	220 - 240 V AC 50/60 Hz
Type of control gear	Electronic ballast standard
Control gear included	yes
Light sharing	Symmetric
Beam angle	Wide beam 41-80°
Light outlet	Direct
Degree of protection (IP)	IP66
Impact strength	IK08
Protection class	I
Luminaire with limited surface temperature, sign „D“	yes
Width	145 mm
Height/depth	101 mm
Length	1573 mm
Filament test according to IEC 60695-2-11	850 °C

Order Data

DEHA no	Type	Item number	EAN	VPE
5935845	FR-Anbauleuchte SPLIXX® 258 EVG	5420-45-0002	4046725360452	1 Piece