

4 046725 360643

Leistungsmerkmale

Die RED Kabelbinder aus reinem Polyamid 6.6 sind universell einsetzbar und eine hervorragende Lösung zum Bündeln und Befestigen von Kabeln und Leitungen oder zur Fixierung anderer Produkte. Die silikon- und halogenfreien RED Kabelbinder, in den Farben natur und schwarz, sind resistent gegen verdünnte, organische Säuren, Öle, Benzin, Salzwasser, Lösungsmittel und Fette. Die Montage der RED Kabelbinder erfolgt manuell von Hand oder mit einem Verarbeitungswerkzeug.

Technische Daten

- Brandschutzklasse: UL 94 V2
- Spezifikation: UL, Lloyd's, DNV-GL

DEHA-Nummer

5948166

Artikelnummer

2110-10-0010

EAN

4046725360643

Kennzeichnung

Allgemeine Daten

Merkmale	
Breite des Bandes	7,6 mm
Bandlänge	280 mm
Banddicke	1,5 mm
Max. Bündeldurchmesser	70 mm
Min. Haltekraft	544 N
Montagetemperatur	IST-/ +40/ SOLL -40 - 85 °C
Ausführung	innenverzahnt
Bandverschluss	Kunststoffzunge/-nase
Werkstoff	Kunststoff
Werkstoffgüte	Polyamid PA
Oberfläche	unbehandelt
Halogenfrei	ja
Farbe	natur
UL-Zulassung	ja


Produktabbildungen

Bestelldaten

DEHA-Nr.	Typ	Artikelnummer	EAN	VPE
5948166	2110-10-0010	2110-10-0010	4046725360643	5000 Stück



Cable tie natural 7.6x280 mm (WxL)



4 046725 360643

Performance features

The RED cable ties made of pure polyamide 6.6 can be used universally and are an excellent solution for bundling and fastening cables and wires or for fixing other products. The silicone and halogen-free RED cable ties, in natural and black, are resistant to diluted organic acids, oils, gasoline, salt water, solvents and grease. The RED cable ties are installed manually by hand or with a processing tool.

Technical data

- Fire protection class: UL 94 V2
- Specification: UL, Lloyd's, DNV-GL

DEHA number

5948166

Item number

2110-10-0010

EAN

4046725360643

label

General Data

Features	
Band width	7,6 mm
Length belt/tape/tie	280 mm
Tie thickness	1,5 mm
Max. bundle diameter	70 mm
Min. holding force	544 N
Mounting temperature	IST-/ +40/ SOLL -40 - 85 °C
Model	Internal toothing
Band closure	Plastic lip/-cam
Material	Plastic
Material quality	Polyamid PA
Surface protection	Untreated
Halogen free	yes
Colour	Natural colour
UL approval	yes

Product pictures

Order Data

DEHA no	Type	Item number	EAN	VPE
5948166	2110-10-0010	2110-10-0010	4046725360643	5000 Piece