Datenblatt

RED®

ÜBERZEUGT. EINFACH.

Kabelbinder schwarz 3,6x200 mm (BxL)



4 046725 360704

Leistungsmerkmale

Die RED Kabelbinder aus reinem Polyamid 6.6 sind universell einsetzbar und eine hervorragende Lösung zum Bündeln und Befestigen von Kabeln und Leitungen oder zur Fixierung anderer Produkte. Die silikon- und halogenfreien RED Kabelbinder, in den Farben natur und schwarz, sind resistent gegen verdünnte, organische Säuren, Öle, Benzin, Salzwasser, Lösungsmittel und Fette. Die Montage der RED Kabelbinder erfolgt manuell von Hand oder mit einem Verarbeitungswerkzeug.

Technische Daten
- Brandschutzklasse: UL 94 V2
- Spezifikation: UL, Lloyd's, DNV-GL

DEHA-Nummer
5948172

Artikelnummer
2110.10.0016

EAN
4046725360704

Kennzeichnung

Kabelbinder schwarz 3,6x200 mm (BxL)

Allgemeine Daten

Merkmale	
Breite des Bandes	3,6 mm
Bandlänge	200 mm
Banddicke	1,2 mm
Max. Bündeldurchmesser	53 mm
Min. Haltekraft	182 N
Montagetemperatur	IST-/+40/SOLL -40 - 85 °C
Ausführung	innenverzahnt
Bandverschluss	Kunststoffzunge/-nase
Werkstoff	Kunststoff
Werkstoffgüte	Polyamid PA
Oberfläche	unbehandelt
UV-stabil nach ASTM D6779	ja
Halogenfrei	ja
Farbe	schwarz
UL-Zulassung	ja

Produktabbildungen

Bestelldaten

DEHA-Nr.	Typ	Artikelnummer	EAN	VPE
5948172	2110-10-0016	2110-10-0016	4046725360704	20000 Stück

Data Sheet

RED®

SIMPLY. CONVINCING.

Cable tie black 3.6x200 mm (WxL)



4 046725 360704

Performance features

The RED cable ties made of pure polyamide 6.6 can be used universally and are an excellent solution for bundling and fastening cables and wires or for fixing other products. The silicone and halogen-free RED cable ties, in natural and black, are resistant to diluted organic acids, oils, gasoline, salt water, solvents and grease. The RED cable ties are installed manually by hand or with a processing tool.

Technical data

- Fire protection class: UL 94 V2
- Specification: UL, Lloyd's, DNV-GL

DEHA number

5948172

Item number

2110-10-0016

EAN

4046725360704

label

Cable tie black 3.6x200 mm (WxL)

General Data

Features	
Band width	3,6 mm
Length belt/tape/tie	200 mm
Tie thickness	1,2 mm
Max. bundle diameter	53 mm
Min. holding force	182 N
Mounting temperature	IST-/+40/SOLL -40 - 85 °C
Model	Internal toothing
Band closure	Plastic lip/-cam
Material	Plastic
Material quality	Polyamid PA
Surface protection	Untreated
UV-stable acc. ASTM D6779	yes
Halogen free	yes
Colour	Black
UL approval	yes

Product pictures

Order Data

DEHA no	Type	Item number	EAN	VPE
5948172	2110-10-0016	2110-10-0016	4046725360704	20000 Piece