Datenblatt

RED®

ÜBERZEUGT. EINFACH.

Kunststoffpanzer-Leerrohr, Type 40, Klassifizierung 33332, 750 N / 5cm



Leistungsmerkmale

Das Kunststoffpanzer-Leerrohr ist insbesondere für Betonverlegung (Stampf- und Rüttelbeton) geeignet und findet beim Einsatz hoher Temperaturen Verwendung.

Technische Daten

- Druckfestigkeit: 750 N/5 cm
- Schlagfestigkeit: mittel, 2,0 kg/100 mm
- DIN EN 61386-1 (VDE0605-1), DIN EN61386-22 (VDE0605-22) und DIN EN 60423
- Flammwidrig, selbstverlöschend sowie korrosionsfest
- Klassifizierung 33332

DEHA-Nummer

6030478

Artikelnummer

2210-20-0015

EAN

4046725398745

Kennzeichnung

Kunststoffpanzer-Leerrohr, Type 40, Klassifizíerung 33332, 750 N / 5cm

Allgemeine Daten

Merkmale	
Werkstoff	Polyolefine
Ausführung flammwidrig	ja
Biegeverhalten	biegsam
Druckfestigkeitsklasse	mittel (Klasse 3)
Schlagfestigkeit	mittel (Klasse 3)
Unterputz	ja
Aufputz	ja
Auf Holz	ja
Hohlwand	ja
Geeignet für Betoninstallation	ja
Maschinen und Anlageninstallation	ja
Unterflurinstallation (Estrich)	ja
Verlegung im Erdreich	ja
Innendurchmesser	31,8 mm
Außendurchmesser	40 mm
Betriebstemperatur	-15 - 105 °C
Farbe	grau

Bestelldaten

DEHA-Nr.	Typ	Artikelnummer	EAN	VPE
6030478	Ku-Le-Ro 105 M40	2210-20-0015	4046725398745	900 Meter

Data Sheet

SIMPLY. CONVINCING.

Plastic armored empty pipe, type 40, classification 33332, 750 N / 5cm



Performance features

The plastic armored empty pipe is particularly suitable for laying concrete (tamped and vibrated concrete) and is used when high temperatures are used.

Technical data

- Compressive strength: 750 N/5 cm
- Impact resistance: medium, 2.0 kg/100 mm
- DIN EN 61386-1 (VDE0605-1), DIN EN61386-22 (VDE0605-22) and DIN EN 60423
- Flame-retardant, self-extinguishing and corrosion-resistant
- Classification 33332

DEHA number

6030478

Item number

2210-20-0015

EAN

4046725398745

label

SIMPLY. CONVINCING.

Plastic armored empty pipe, type 40, classification 33332, 750 N / 5cm

General Data

Features	
Material	Polyolefin
Fire retardant version	yes
Bending strength	Pliable
Compressive strength class	Medium (class 3)
Impact strength	Medium (class 3)
Flush mounted (plaster)	yes
Surface mounted	yes
Suitable for installation on wood	yes
Hollow wall	yes
Suitable for concrete installation	yes
Machine and systems installation	yes
Suitable for subsurface installation (screed))	yes
Underground installation	yes
Inner diameter	31,8 mm
Outer diameter	40 mm
Operation temperature	-15 - 105 °C
Colour	Grey

Product pictures

Order Data

DEHA no	Type	Item number	EAN	VPE
6030478	Ku-Le-Ro 105 M40	2210-20-0015	4046725398745	900