




LED Ein- und -Aufbau Notleuchte WALK ME[®] 3 W,
6500 K, IP20/40, 3 h Laufzeit, inkl. 4 Wechsellinsen



4 046725 398813

Leistungsmerkmale

Die LED-Notleuchte WALK ME[®] dient der Notbeleuchtung von Rettungswegen. Bei einem Ausfall der Netzspannung schaltet sie auf Notlichtbetrieb um und wird durch den eingebauten Lithium-Ionen Akku versorgt. Die Notlichtdauer beträgt wahlweise 3 Stunden mit 220 lm oder 8 Stunden mit 130 lm.

Mit den vier Linsenoptiken kann der Abstrahlwinkel auf Raum- oder Korridorbeleuchtung, eng oder weit angepasst werden. Die Notleuchte WALK ME[®] verfügt über automatische und manuelle Selbsttestfunktionen. Die Statusanzeige erfolgt über zwei Status-LEDs.

Die Leuchte eignet sich zur Einbau- oder Aufbau- montage. Eine Aufputz-Ringblende zur Aufbaumontage wird mitgeliefert. Die LED-Notleuchte WALK ME[®] ist für Bereitschaftsschaltung ausgelegt.

Lieferumfang:

LED-Notleuchte mit Akku, Leuchtengehäuse, Aufputz-Ringblende, 4 Linsenoptiken, Montagematerial

Technische Daten

- Notlichtdauer: wahlweise 3 h mit 220 lm oder 8 h mit 130 lm
- Selbsttest: automatisch und manuell
- Statusanzeige
- 4 Linsenoptiken (360° weit, 360° eng, direktional weit, direktional eng)
- Schaltschwelle: > 0,3 s unter 166 V
- 3 W LED/6500 K
- Umgebungstemperatur: 0 °C bis +40 °C
- Erstladezeit: 20 Stunden

DEHA-Nummer

6087153

Artikelnummer

5610-10-0002

EAN

4046725398813

Kennzeichnung

LED Ein- und -Aufbau Notleuchte WALK ME[®] 3 W, 6500 K, IP20/40, 3 h Laufzeit, inkl. 4 Wechsellinsen

Allgemeine Daten


Merkmale	
Montageart	Aufbau/Einbau
Art der Kennzeichnung	nicht zutreffend
Überwachungseinrichtung	Prüftaste
Schaltungsart	Bereitschaftsschaltung
Einspeisung	dezentral (Einzelbatterie)
Akkubeschaffenheit	Lithium-Ionen 3,6 V, 2,6 Ah
Leuchtmittel	LED nicht austauschbar
Mit Leuchtmittel	ja
Werkstoff des Gehäuses	Kunststoff
Gehäusefarbe	weiß
Werkstoff der Abdeckung	ohne Abdeckung
Spannungsart	AC
Nennspannung	220 - 240 V AC 50/60 Hz
Bemessungslebensdauer L70/B10 bei 25 °C	50000 h
Schutzart (IP)	IP40 Aufbau/IP20 Einbau
Schutzklasse	II
Farbtemperatur	6500 K
Erkennungsweite	18 m
Höhe/Tiefe	46 mm
Außendurchmesser	130 mm
Einbaudurchmesser	115 mm

Bestelldaten

DEHA-Nr.	Typ	Artikelnummer	EAN	VPE
6087153	Walk Me [®]	5610-10-0002	4046725398813	1 Stück



LED built-in and surface-mounted emergency light WALK ME[®] 3 W, 6500 K, IP20/40, 3 h runtime, including 4 interchangeable lenses



4 046725 398813

Performance features

The WALK ME[®] LED emergency light is used for emergency lighting of escape routes. If the mains voltage fails, it switches to emergency lighting mode and is powered by the built-in lithium-ion battery. The emergency lighting duration is either 3 hours with 220 lm or 8 hours with 130 lm.

With the four lens optics, the beam angle can be adjusted to narrow or wide room or corridor lighting. The WALK ME[®] emergency light has automatic and manual self-test functions. The status is displayed via two status LEDs.

The luminaire is suitable for recessed or surface mounting. A surface-mounted ring cover for surface mounting is included. The WALK ME[®] LED emergency light is designed for standby switching.

Scope of delivery:

LED emergency light with battery, light housing, surface-mounted ring cover, 4 lens optics, mounting material

Technical data

- Emergency lighting duration: either 3 hours with 220 lm or 8 hours with 130 lm
- Self-test: automatic and manual
- Status display
- 4 lens optics (360° wide, 360° narrow, directional wide, directional narrow)
- Switching threshold: > 0.3 s below 166 V
- 3W LED/6500K
- Ambient temperature: 0°C to +40°C
- Initial charging time: 20 hours

DEHA number

6087153

Item number

5610-10-0002

EAN

4046725398813

label

LED built-in and surface-mounted emergency light WALK ME[®] 3 W,
6500 K, IP20/40, 3 h runtime, including 4 interchangeable lenses

General Data

Features	
Mounting method	Surface mounting/recessed mounting
Type of indicator	Not applicable
Monitoring equipment	Test button
Wiring system	Standby switching
Power supply system	Peripheral (individual battery)
Battery quality	Lithium-Ionen 3,6 V, 2,6 Ah
Lamp type	LED not exchangeable
With light source	yes
Material housing	Plastic
Colour housing	White
Material cover	Without cover
Voltage type	AC
Nominal voltage	220 - 240 V AC 50/60 Hz
Rated life time L70/B10 at 25 °C	50000 h
Degree of protection (IP)	IP40 construction/IP20 installation
Protection class	II
Colour temperature	6500 K
Recognition distance	18 m
Height/depth	46 mm
Outer diameter	130 mm
Built-in diameter	115 mm

Order Data

DEHA no	Type	Item number	EAN	VPE
6087153	Walk Me [®]	5610-10-0002	4046725398813	1 Piece