Datenblatt

RED®

ÜBERZEUGT. EINFACH.

Putzausgleichsring PAR 1260, Ø 60 mm T 12 mm, Schraubabstand 60 mm



Leistungsmerkmale

Der RED Putzausgleichsring wird zum Ausgleich von tiefsitzenden Geräte- und Verbindungsdosen genutzt. Die Putzausgleichsringe mit gleichem Durchmesser können aufeinander montiert werden. Die vormontierte Geräteschraube hat eine Länge von 15 mm.

Technische Daten

- Max. rel. Luftfeuchte bei 25 °C (kurzfristig) = 90 %
- Max. rel. Luftfeuchte bei 40 °C = 50 %
- Umgebungstemperatur (24 h) = 35 °C
- Umgebungstemperatur min./max. = -25 °C/+40 °C

DEHA-Nummer

6525625

Artikelnummer

2260-10-0016

EAN

4046725400547

Kennzeichnung

Putzausgleichsring PAR 1260, Ø 60 mm T 12 mm, Schraubabstand 60 mm

Allgemeine Daten

Merkmale	
Ausgleichshöhe	12 mm
Durchmesser	60 mm
Form	rund
Anwendung	Einbaudose
Montageart	Unterputz

Produktabbildungen

Bestelldaten

DEHA-Nr.	Typ	Artikelnummer	EAN	VPE
6525625	PAR 1260	2260-10-0016	4046725400547	50,00 Stück

Data Sheet

SIMPLY. CONVINCING.

Plaster compensation ring PAR 1260, Ø 60 mm D 12 mm, screw spacing 60 mm



Performance features

The RED plaster compensation ring is used to compensate for deep-seated device and connection boxes. The plaster compensation rings with the same diameter can be mounted on top of each other. The pre-assembled device screw has a length of 15 mm.

Technical data

- Max. rel. Humidity at 25 °C (short term) = 90%
- Max. rel. Humidity at 40 °C = 50%
- Ambient temperature (24 h) = 35 °C
- Ambient temperature min./max. = -25°C/+40°C

DEHA number

6525625

Item number

2260-10-0016

EAN

4046725400547

label

SIMPLY. CONVINCING.

Plaster compensation ring PAR 1260, Ø 60 mm D 12 mm, screw spacing 60 mm

General Data

Features	
Levelling height	12 mm
Diameter	60 mm
Shape	Round
Application	Built-in installation box
Mounting method	Flush mounted (plaster)

Product pictures

Order Data

DEHA no	Type	Item number	EAN	VPE
6525625	PAR 1260	2260-10-0016	4046725400547	50,00 Piece