Datenblatt

RED®

ÜBERZEUGT. EINFACH.

Kontaktspray 300 ml



4 046725 401056

Leistungsmerkmale

Rostlockerung und Vorbeugung gegen weiteres Verrosten. Das Kontakt-Spray wirkt wasserverdrängend – daher auch für elektrische Kontakte an Kraftfahrzeugen bei Zündstörungen verwendbar (Unterbrecher). Gegen Quietsch- und Pfeifgeräusche bei Stoßdämpfern, Kettenantrieben und Aufhängungen. Es reinigt Teerflecke auf Kraftfahrzeuglackierungen, pflegt und schützt Chromteile des PKW. Das Kontakt-Spray dient zur Entfernung loser Oxid- und Abbrandreste, sowie Staubablagerungen oder Verschmutzungen beweglicher Kontaktbereiche.

Technische Daten:
- Temperaturbeständigkeit: - 20 °C bis + 250 °C
- Mineralölprodukt/silikonfrei

Verarbeitung:
Werkstücke gezielt einsprühen, kurz einwirken lassen. Bei Bedarf wiederholen.

Entsorgung:
Behältnisse nach Gebrauch nicht in den Restmüll geben. Nur restentleerte Behältnisse zum Recycling geben.

Besondere Hinweise:
Weitere Hinweise zur Produktsicherheit und Handhabung entnehmen Sie bitte unserem Sicherheitsdatenblatt.

Haltbarkeit:
Das Produkt unterliegt keiner Mindesthaltbarkeit. Gewährleistung entsprechend der gesetzlichen Gewährleistungspflicht.

DEHA-Nummer
6934378

Artikelnummer
2130-20-0009

EAN
4046725401056

Kennzeichnung

RED®

ÜBERZEUGT. EINFACH.

Kontaktspray 300 ml

Allgemeine Daten

Merkmale	
Einsatzbereich	sonstige
Funktion	Kontaktfett
Inhalt	300 ml
Brennbar	ja
Bleifrei	ja
Chromatfrei	ja

Bestelldaten

DEHA-Nr.	Typ	Artikelnummer	EAN	VPE
6934378	2130-20-0009	2130-20-0009	4046725401056	1 Dose

Data Sheet

RED®

SIMPLY. CONVINCING.

Contact Spray 300 ml



4 046725 401056

Performance features

Loosening rust and preventing further rusting. The contact spray has a water-displacing effect - therefore it can also be used for electrical contacts on motor vehicles in the event of ignition problems (breakers). Against squeaking and whistling noises in shock absorbers, chain drives and suspensions. It cleans tar stains on motor vehicle paintwork, cares for and protects chrome parts of the car. The contact spray is used to remove loose oxide and burn-off residues, as well as dust deposits or dirt from moving contact areas.

Technical data:

- Temperature resistance: - 20 °C to + 250 °C
- Mineral oil product/silicone-free

Processing:

Spray workpieces in a targeted manner and let it work for a short time

let. Repeat if necessary.

Disposal:

Do not throw containers into the trash after use. Only send empty containers for recycling.

Special instructions:

Further information on product safety and handling can be found in our safety data sheet.

Durability:

The product is not subject to a minimum shelf life. Warranty in accordance with the statutory warranty obligation.

DEHA number

6934378

Item number

2130-20-0009

EAN

4046725401056

label

SIMPLY. CONVINCING.

Contact Spray 300 ml

General Data

Features	
Application range	Other
Function	Contact grease
Volume	300 ml
Combustible	yes
Lead free	yes
Chromate free	yes

Order Data

DEHA no	Type	Item number	EAN	VPE
6934378	2130-20-0009	2130-20-0009	4046725401056	1 can