




LED-Treiber für CUBEXX[®] LED Panel 900 mA, 36 W,
flackerfrei, 220-240 V AC, 50/60 Hz



4 046725 401186

Leistungsmerkmale

Zuverlässiger LED-Treiber geeignet für 36 W Leistung. Der Ausgang liefert 900 mA Konstantstrom. Farbtemperatur ist schaltbar und Licht ist flackerfrei.

Technische Daten

- Eingangsspannung 220-240 V AC, 50/60 Hz
- Eingangsstrom 0,17 A
- Einschaltstrom 30 A max.
- Effizienz 90 %
- Powerfaktor >0,9
- Eingangsleistung 40 W max.
THD < 15 % bei Volllast
- Ausgangsspannung 25-40 V
- Ausgangsstrom 900 mA (Konstantstrom)
- Ausgangsleistung 36 W
- Nicht dimmbar
- Schutzfunktionen: Kurzschluss, Überspannung (max. 55 V), Übertemperatur
- Betriebstemperatur
-20° bis +45°C (10 %–90 % RH)
- Lagertemperatur: -40° bis +85°C (5 %–95 % RH)
- Schutzart IP20
- Schutzklasse II
- Gehäusetemperatur Ta: 45 °C / Tc: 80 °C
- Kabel 120 mm, 0,5 mm²
- Maße 125x40x27 mm

DEHA-Nummer

6994037

Artikelnummer

5630-10-0002

EAN

4046725401186

Kennzeichnung



LED-Treiber für CUBEXX[®] LED Panel 900 mA, 36 W,
flackerfrei, 220-240 V AC, 50/60 Hz

Allgemeine Daten


Merkmale			
Länge	125 mm	Ausgangsstrom	900 mA
Breite	40 mm	Ausgangsleistung	36 W
Höhe	27 mm	Schutzart (IP)	IP20
Ohne Dimmfunktion	ja	Schutzklasse	II
Geeignet für Konstantstrom	ja		
Ausgangsspannung	25 - 40 V		

Bestelldaten

DEHA-Nr.	Typ	Artikelnummer	EAN	VPE
6994037	LED-Treiber für CUBEXX [®]	5630-10-0002	4046725401186	1 Stück



LED driver for CUBEXX[®] LED panel, 900 mA, 36 W,
flicker-free, 220–240 V AC, 50/60 Hz



4 046725 401186

Performance features

Reliable LED driver suitable for 36 W power output.
The output delivers 900 mA constant current.
Selectable color temperature; flicker-free light.

Technical Data

- Input voltage: 220–240 V AC, 50/60 Hz
- Input current: 0.17 A
- Inrush current: 30 A max.
- Efficiency: 90%
- Power factor: >0.9
- Input power: 40 W max. THD: <15% at full load
- Output voltage: 25–40 V
- Output current: 900 mA (constant current)
- Output power: 36 W
- Non-dimmable
- Protection functions: Short circuit, overvoltage (max. 55 V), overtemperature
- Operating temperature: -20° to +45°C (10%–90% RH)
- Storage temperature: -40° to +85°C (5%–95% RH)
- Ingress protection: IP20
- Protection class: II
- Housing temperature: Ta: 45°C / Tc: 80°C
- Cable: 120 mm, 0.5 mm²
- Dimensions: 125x40x27 mm

DEHA number

6994037

Item number

5630-10-0002

EAN

4046725401186

label



LED driver for CUBEX[®] LED panel, 900 mA, 36 W,
flicker-free, 220–240 V AC, 50/60 Hz

General Data

Features			
Length	125 mm	Output current	900 mA
Width	40 mm	Output power	36 W
Height	27 mm	Degree of protection (IP)	IP20
No dim function	yes	Protection class	II
Suitable for constant current	yes		
Output voltage	25 - 40 V		

Order Data

DEHA no	Type	Item number	EAN	VPE
6994037	LED-Treiber für CUBEX [®]	5630-10-0002	4046725401186	1 Piece