




1Ph18-45A digitaler Stromzähler



4 046725 401414

Leistungsmerkmale

Der digitale Wechselstromzähler 1Ph18-45A für die Hutschiene (1 TE) mit 6-Segment LCD-Display für Direktanschluss, misst die Wirkleistung der fließenden Ströme (Nennstrom 5 A) (Grenzstrom 45 A) SO-Schnittstelle mit 1000 Imp/kWh

Technische Daten

- Anlaufstrom: Ist < 0,004 Iref
- Spannungspfad: < 2 W
- Betriebstemperatur: -20 °C bis +50 °C
- Lagertemperatur: -30 °C bis +70 °C
- Anzeige: LCD 6-stellig
- Umfang der Anzeige: Wirkverbrauch
- Schutzklasse: II
- Material: Glasfaser verstärktes Polycarbonat
- MID geeicht
- Gewicht: ca. 0,1 kg

DEHA-Nummer

7120783

Artikelnummer

2810-30-0001

EAN

4046725401414

Kennzeichnung

Allgemeine Daten


Merkmale	
Zählertyp	elektronisch
Nennstrom (In)	5 A
Maximalstrom (Imax)	45 A
Nennspannung (Un) N-L	230 V
Frequenz	50 - 60 Hz
Leistungsaufnahme	1 W
Genauigkeitsklasse	A
Polart	1-phasig
Ausführung	Direktmessung
Energieart	Wirkleistung
Geeignet für	Bezug
Tarifausführung	Eintarif
Tarifsteuerung	extern
Rücklaufsperre	ja
Geeicht	ja
Zulassung	Measuring Instruments Directive
Impulsausgang	optisch
Impulsart	S0
Impulsrate	1000 Imp/kWh (kvarh)
Anzeigeart	digital
Montageart	REG
Breite in Teilungseinheiten	1
Breite	118 mm
Tiefe	18 mm
Höhe	64 mm
Anzahl der Stellen	6
Schutzart (IP)	IP51

Bestelldaten

DEHA-Nr.	Typ	Artikelnummer	EAN	VPE
7120783	1Ph18-45A digitaler Zähler	2810-30-0001	4046725401414	10 Stück



1Ph18-45A digital electricity meter



4 046725 401414

Performance features

The digital alternating current meter 1Ph18-45A for the DIN rail (1 HP) with 6-segment LCD display for direct connection, measures the active power of the flowing currents (rated current 5 A) (limit current 45 A) S0 interface with 1000 Imp/kWh

Technical data

- Starting current: < 0.004 I_{ref}
- Voltage path: <2 W
- Operating temperature: -20 °C to +50 °C
- Storage temperature: -30 °C to +70 °C
- Display: LCD 6-digit
- Scope of display: active consumption
- Protection class: II
- Material: glass fiber reinforced polycarbonate
- MID calibrated
- Weight: approx. 0.1 kg

DEHA number

7120783

Item number

2810-30-0001

EAN

4046725401414

label

1Ph18-45A digital electricity meter**General Data**

Features	
Type of meter	Electronic
Nominal current (In)	5 A
Max. current (Imax)	45 A
Nominal voltage (Un) N-L	230 V
Frequency	50 - 60 Hz
Power consumption	1 W
Accuracy class	A
Pole type	Single phase
Model	Direct measurement
Energy type	Effective power
Suitable for	Purchase
Tariff type	One-tariff
Tariff control	External
Escapement mechanism	yes
Calibrated	yes
Approval	Measuring Instruments Directive
Pulse output	Optic
Pulse type	S0
Pulse rate	1000 Imp/kWh (kvarh)
Type of indication	Digital
Mounting method	DRA (DIN-rail adapter)
Width in number of modular spacings	1
Width	118 mm
Depth	18 mm
Height	64 mm
Number of positions total (counter)	6
Degree of protection (IP)	IP51

Order Data

DEHA no	Type	Item number	EAN	VPE
7120783	1Ph18-45A digitaler Zähler	2810-30-0001	4046725401414	10 Piece