Datenblatt

RED®
ÜBERZEUGT. EINFACH.

Universalband 50x0,18 mmx50 m, PE-Folie mit Gewebe, Silbergrau



4 046725 403586

Leistungsmerkmale

Das Universalband dient als Standardmontageklebeband. Es dient ideal zum Abkleben von Rohren und Lüftungsschächten sowie zum Befestigen von Folien auf Metall, Kunststoff, Putz und Beton. Es kann auch zum Versiegeln als Schutz vor Feuchtigkeitseinwirkung eingesetzt werden. Außerdem wird es im Automobilbau für Bandagierung von Kabelsätzen, die Feuchtigkeit und Spritzwasser ausgesetzt sind, verwendet.

Verarbeitungsempfehlung:

Bringen Sie das Klebeband unmittelbar nach dem Abrollen auf diezu beklebende Oberfläche und drücken es fest an. Die besten Ergebnisse werden bei einer Verarbeitungstemperatur zwischen 20 und 24 °C erzielt.

Bemerkung:

Die zubeklebende Oberfläche muss frei von Öl oder anderen Oberflächenverschmutzungen wie Puder, Schmutz oder Trennmittel sein. Die Klebkraft kann beeinträchtigt werden, wenn die beklebten Substrate Weichmacher enthalten. Diese Angaben geben wir nach bestem Wissen, jedoch ohne Gewähr. Die Tauglichkeit der Produkte für den endgültigen Einsatzzweck sollte durch Vorversuche beim Anwender überprüft werden. Die angegebenen Werte sind statistische Mittelwerte.

DEHA-Nummer

7818709

Artikelnummer

2130-10-0016

EAN

4046725403586

Kennzeichnung

PVC-FREI

Universalband 50x0,18 mmx50 m, PE-Folie mit Gewebe, Silbergrau

Allgemeine Daten

Merkmale			
Breite	50 mm	Farbe	Silber
Länge	50 m	Werkstoff	Polyethylen (PE)
Stärke	0,18 mm	Von Hand abreißbar	ja
Temperaturbeständigkeit	-40 - +80 °C		

Bestelldaten

DEHA-Nr.	Typ	Artikelnummer	EAN	VPE
7818709	Universalband	2130-10-0016	4046725403586	24 Stück

Data Sheet

RED®

SIMPLY. CONVINCING.

Universal tape 50 x 0.18 mm x 50 m, PE film with fabric reinforcement, silver-grey



4 046725 403586

Performance features

This universal tape serves as a standard mounting adhesive tape. It is ideal for masking pipes and ventilation ducts, as well as for securing sheeting to metal, plastic, plaster, and concrete. It can also be used to create a moisture-resistant seal. Additionally, it is used in automotive manufacturing to wrap cable harnesses exposed to moisture and splash water.

Application recommendations:

Apply the tape to the target surface immediately after unrolling and press it down firmly. Best results are achieved at an application temperature between 20 and 24°C.

Note:

The surface to be taped must be free of oil and other contaminants such as powder, dirt, or release agents. Adhesion may be impaired if the substrates contain plasticizers. We provide this information to the best of our knowledge, but without guarantee. Users should verify the suitability of the products for their specific application through preliminary testing. The values provided are statistical averages.

DEHA number

7818709

Item number

2130-10-0016

EAN

4046725403586

label

PVC-FREI

SIMPLY. CONVINCING.

Universal tape 50 x 0.18 mm x 50 m, PE film with fabric reinforcement, silver-grey

General Data

Features			
Width	50 mm	Colour	Silver
Length	50 m	Material	Polyethylene (PE)
Thickness	0,18 mm	Von Hand abreißbar	yes
Temperature resistance	-40 - +80 °C		

Order Data

DEHA no	Type	Item number	EAN	VPE
7818709	Universalband	2130-10-0016	4046725403586	24 Piece